



Brisa[®] | Original



Acoustical properties • Breathable technology



Acoustical



Breathable



Custom

Brisa® | Original




533-1359 Strawberry




533-5747 White



533-3277 Moon



533-3276 Wishbone



533-3275 Gravel



533-5802 Ash



533-3866 French Vanilla



533-3019 Birch



533-3822 Bone




533-3946 New Sand



533-3915 Putty



533-3863 Cream




533-3864 Desert Clay




533-3233 Honeycomb




533-3867 Golden




533-3051 Ginger



533-3823 Aztec




533-8202 Koi




533-8245 Cinnabar



533-3591 Caramel



533-3200 Peat



533-8203 Flamingo



533-1359 Strawberry



533-1383 Pompeiian Red



533-1373 Salsa



533-3825 Canyon



533-1344 Rose Red



533-1361 Beet Root



533-9374 Blossom



533-9400 Cabernet



533-9378 Abyss



533-3914 Bark




533-3022 Shiitake



533-3913 Truffle



533-3023 Coffee Bean



533-9310 Hazy Lilac




533-5820 Quicksilver




533-3234 Cookie Dough




303-4510 Celery



533-4487 Sage



533-4488 Olive




533-2698 Sterling Blue




533-2697 Mineral



533-4448 Apple Green




533-4302 Esmeralda




533-4303 Seaweed




533-3272 Iceberg




533-2523 Turq




533-2696 Skyway



533-2645 Cambridge Blue




533-2621 Blue Sea




533-5703 Wrought Iron



533-2694 Night Navy



533-2620 Evening Blue



533-2683 Indigo



533-5749 Black Onyx



Acoustical



Breathable



Custom

Brisa® | Original

General Specifications

Composition:

100% Polycarbonate Polyurethane Surface
65% Polyester, 35% Rayon Backing

Weight:

Approx. 9.3 oz. Per Square Yard
Approx. 315 Grams Per Square Metre

Thickness:

Approx. 1.0 Millimetres

Width:

54 Inches / 137 Centimetres

Performance

Abrasion:

ASTM D4157 / 300,000 Double Rubs (Wyzenbeek)*
BS 2543 / 160,000 Rubs (Martindale)*

*meets or exceeds

Hydrolysis:

14+ Weeks
ASTM D3690-02 Sect. 6.11 (Hydrolytic Stability)
ISO 1419 Method C (Accelerated Ageing)

Adhesion of Coating:

ASTM D751

Tear Strength:

ASTM D2261

Breaking Strength:

ASTM D5034

Air Permeability:

ASTM D737

Sound Absorption:

ASTM C423

Colorfastness

Light Fastness:

AATCC 16.3, 200 Hours, Grade 4-5

Crocking:

AATCC 8, Class 5 Wet & Dry

Flammability

F/R Rating:

- ASTM E84 (Adhered) - Class A
- CA TB 117-2013 - Pass
- FMVSS 302 & 95/28 Annex IV - Pass
- NFPA 260 - Class 1
- UFAC - Class 1

Other Tests*:

- ASTM E84 (Unadhered)
- BS 5852 PT 0, 1 & 5 (Crib 5)
- BS 5867 Part 2 Type B
- BS 7175
- California Technical Bulletin 133
- FAR Specifications
- IMO A.652 (16)
- NFPA 701

*These fabrics, when treated and/or used with other compatible furniture components, have been shown to perform under these fire test conditions.

Earth Friendly

• GREENGUARD Certified

- Meets stringent chemical emission limits for various VOCs (ex. Formaldehyde)
- Promotes healthier indoor air quality
- Contributes towards satisfying credits under LEED® and BIFMA

• Compliant with Prop 65

- No Bisphenol A (BPA)
- No Conflict Minerals
- No Flame Retardants (Halogenated, Brominated: ex. PBDEs)
- No Heavy Metal Stabilizers
- No Plasticizer Phthalates
- No POPs (Persistent Organic Pollutants)
- No PVC (Polyvinyl Chloride)
- No toxic by-products
- Over 99% of solvents recaptured and recycled

For more information on our fabrics, cleaning and care instructions, please visit our website.



PRODUCT
CERTIFIED FOR
LOW CHEMICAL
EMISSIONS:
UL.COM/IGG
UL 2818

Ultrafabrics® and logo, and Brisa® are trademarks of Ultrafabrics Inc. Made in Japan.

ultrafabricsinc.com



11/17